Appalachian Mountain Speedweek Technical Bulletin 13-01 Release January 24, 2013

ENGINE RULES AND ENGINE SET-BACK

A. Only conventional type V-8 engines with the cam in the block will be permitted. There will be no limit on the cubic inch displacement.

B. Engines must be based on a factory design and must be naturally aspirated.

Aluminum or steel blocks permitted.

C. No fuel injection devices, electric fuel pumps, turbo chargers, or blowers permitted.

D. Magnetos are permitted. However, the engine must have an operating self starter.

E. A maximum of twenty five and one-half (25-1/2") inches from the center of the ball joint to

the front of the motor plate/engine bell housing flange will be permitted.

F. Carburetor is limited to one four barrel.

G. All engines are limited to one spark plug and two valves per cylinder.

H. No engines using coil packs are allowed. Engine must operate using a single distributor. No distributor-less engines allowed

I. No overhead cam engines.

ELECTRONIC AND TRACTION CONTROL DEVICES

A. All electronic or computerized wheel spin or acceleration retardation traction control devices are strictly prohibited. Controlled timing devices attached to or controlling accelerator or rotation of wheel are strictly prohibited.

B. All traction control devices utilizing wheel sensors or any means of measuring ground speed to control wheel spin are strictly prohibited.

C. Adjustable ping control devices, dial a chip controls, timing controls or automated throttle controls are not permitted in cockpit or any other driver accessible areas.

D. Any remotely controlled components inside or outside the cockpit of any competitor's racecar are NOT permitted.

F. Radios or devices for transmitting voice or data are prohibited, either in the racecar or on anyone connected with the car.

WEIGHT

A. The total weight of the car with the driver will be; A minimum of 2,250 lbs as weighed on the track scales.

B. All weights must be painted white and clearly labeled with the car number on it.

C. Any weight(s) must be securely attached to the frame below the body decking.

D. Weights attached to the rear bumper and/or outside the frame will not be permitted.

E. Pellet-type and/or liquid-type weight/ballast will not be permitted.

F. Cars not making weight will be disqualified.

END.